

Type	
Project	
Notes	



## ARL-CV3F

### Rigid Strip Light

Slim profile that can be used for many applications

Anodized aluminum profile and perforated mask

IP65 rated

Stainless steel brackets

DMX control with auto-addressing features

Colour variation within 3-step MacAdam



## PRODUCT SPECIFICATIONS

Summary	ARL-48CV3F	ARL-24CV3F	ARL-12CV3F
LED Quantity	48	24	12
Power Rating	11.52 W	5.76 W	2.88 W
Luminous Flux	864 lm	432 lm	216 lm
Dimensions (mm)	1000 x 20 x 17.5	500 x 20 x 17.5	251 x 20 x 17.5
Weight	0.39kg	0.2kg	0.1kg
Luminous Efficacy	75 lm/W		
Viewing Angle	>110 °		
Input Voltage	24V DC		
Operating Temperature	-40°C~50°C		
Life Span	> 50000 hours		
IP	65		
Warranty	5 years		

Ingress Protection	Input Voltage
--------------------	---------------



Recessed Cove Cornish Landscape

CREE  
OSRAM  
LUMILEDS




LED Type



RGBW




Seamless Light



## ORDER FORM

ARL	-CV3F			
1	2	3	4	5
1. FAMILY	2. LED Quantity	3. Voltage	4. CCT	5. MOUNTING OPTIONS
ARL-XXCV3F	12 12 24 24 48 48	1 24V DC	27 2700K 30 3000K 40 4000K 50 5000K	B Blue A Amber R RGB W RGB + White
				1 Surface 2 Tilt 3 Snap-It

## INSTALLATION GUIDE



## PHOTOMETRY

Lamp Source: CREE SMD 3535  
Beam Angle: 110°

Note: Test data is based on  
CV3F-M1000-0048CTA-00 only

