

Type	
Project	
Notes	



AVL-L74102-UD

Honeycomb Luminaire

- Aluminum 6063 casing and PMMA diffuser
- Aluminum die-casting alloy end caps
- Anti-glare control
- Suspension mounted
- Bilateral, offers direct and indirect lighting
- Includes 1.5m mounting cable



PRODUCT SPECIFICATIONS

Summary	AVL-L74102-UD Direct / Down	AVL-L74102-UD Indirect / Up
Dimensions (mm)	1161 x 74 x 102	
Power Consumption	30 W	15 W
Lumen Output	2774 lm	1183 lm
Efficacy	92 lm/W	78 lm/W
CRI	> 80	
Voltage	120 - 277V AC, 347V AC	
Colour Temperature	3000k, 3500k, 4000k	
UGR	18	
IP	20	
Warranty	5 years	



units in mm

ORDER FORM

AVL-L74102					
1	2	3	4	5	6
I. FAMILY	2. SIZE	3. VOLTAGE	4. CCT	5. CCT	6. COLOUR
AVL-L74102	U Up/ Indirect D Down/ Direct	A 120-277V AC B 347V AC	<i>Down / Direct</i> 30 3000K 35 3500K 40 4000K	<i>Up / Indirect</i> 30 3000K 35 3500K 40 4000K	1 White 2 Silver 3 Black 4 Custom