

Type

Project

Notes



AP-AV2SSF

Ultra-Thin Profile Square Regressed Shower Trim

Housing-free light engine install quickly.

The perfect option for a flush finish with ceiling materials.


Ease of installation, fast-mount features.



IP65
RATED & TESTED

5 YEARS
LIMITED WARRANTY
INCLUDED

TECHNICAL DRAWING



Units in Metric

PRODUCT SPECIFICATIONS

Summary	AP-AV2SSF-AR
Dimensions	79mm x 79mm x 116mm
Power Consumption	14 W
Lumen Output	823 lm
Input Voltage	120-277V AC
Colour Temperature	2700K, 3000K, 3500K, 4000K
Finish	Gold, Chrome, Brushed Chrome, Matte White, Brushed Nickel, Satin Nickel, Matte Black, Aluminum
CRI	Ra90
Beam Angle	48° (Flood)
Warranty	5 Years

ORDER FORM

1	2	3	4	5	6	7	8
1. FAMILY	2. SIZE	3. WATTAGE	4. VOLTAGE	5. CCT	6. BEAM ANGLE		
AP-AV2SSF	AR 79 x 79 x 116	14 14W	A 120-277V AC	27 2700K 30 3000K	35 3500K 40 4000K	48 48°	
7. DIMMING	8. FINISH						
DM 0-10V Dimming TRI TRIAC Dimming	CH Chrome AL Aluminum	BC Brushed Chrome BN Brushed Nickel	WH White BK Black	GD Gold SN Satin Nickel			

Type

Project

Notes



ADVANT
LIGHTING

OPTIONS & ACCESSORIES

MOUNTING PLATE

Ideal for unfinished basements and other renovation projects
Choice of Square or Round for 2.5" Remodel housings
Adjustable mounting bars included.



PA2NW 2.5" Square, 2.5" Round

LENSES

Choice of replacement lenses for on-site modification of light diffusion.
Shower Light trims available only with Frosted lens.
*Wall Wash trims available only with Frosted/Frosted lens.



CL Clear



FR Frosted



WW Wall Wash



LN Linear



SL Solite



PR Prismatic



HC Honeycomb



Type

Project


Notes



ADVANT
LIGHTING


HOUSINGS

IC AIR TIGHT HOUSING



ICAT0S2-V14


ICAT	0	S	2	V	14
1. MODEL	2. HOUSING	3. TYPE	4. SERIES	5. DRIVER	6. PERFORMANCE
ICAT Insulated Housing Air Tight	0 254 x 254 (10" x 10")	S Square	2 2-1/2"	V 120-277V AC	14 14 W 1300 lm



ICAT0R2-V14

ICAT	0	R	2	V	14
1. MODEL	2. HOUSING	3. TYPE	4. SERIES	5. DRIVER	6. PERFORMANCE
ICAT Insulated Housing Air Tight	0 254 x 254 (10" x 10")	R Round	2 2-1/2"	V 120-277V AC	14 14 W 1300 lm

REMODEL HOUSING



REA2-V1

REA	2	V	1
1. MODEL	2. SERIES	3. DRIVER	4. PERFORMANCE
REA Remodel Housing	2 2-1/2"	V 120-277V AC	1 1300 lm (1000 lm with 2-1/2")